

# QUICK-SHIP

Basic Quality - Just in Time



The Quick-Ship Program - designed to fill immediate needs with four of Par-Kut's most frequently requested booths.



# QUICK-SHIP

The Quick-Ship Series is Par-Kut's answer to "Just-in-Time" delivery of quality steel buildings for customers' immediate requirements. Standard models in the most requested sizes (3'x4', 4'x6', 4'x7' and 6'x8') have been built and warehoused - waiting for customer order. Within days of order, Quick-Ship booths are

painted to designated color and expedited to site location. Approximate delivery time is 14 days. All materials and specifications of the PAR-KUT Standard are consistent with Quick-Ship booths. Due to time restraints, options are limited to tinted glass, sliding door window, additional duplex outlets, thru wall air conditioner and heater upgrade.

## SPECIFICATIONS

- 2.1 Short form specification: Pre-assembled booth unit(s) shall be Model \_\_\_\_\_ (Model is determined by length first then width. i.e. 6' x 8' booth is model 86) as manufactured by Par-Kut International, Inc.
- 2.2 Structure: Prefabricated steel building shall be single unit welded steel construction with 14-gauge galvanized steel panels and tubing on the exterior and 18-gauge galvanized steel interior panels. Building to be shipped completely assembled. All welded joints ground smooth. Aluminum or fiberglass construction not acceptable.
- 2.3 Base and floor: Base height shall be 4 inches for outside use. Floor shall be 12-gauge galvanized steel, 4-way tread plate. Four 1/4" steel angle iron anchor clips with pre-drilled holes are provided to secure building. Anchors provided by installer shall be galvanized or stainless steel.
- 2.4 Door(s) shall be top suspended sliding aluminum type, fully weather stripped. Include manufacturer's standard lock, glazing and hardware.
- 2.5 Windows: Shall be clear anodized aluminum construction and include glazing and all hardware as required. Provide sliding windows as shown on drawings for ventilation and/or transaction purposes. Include insect screens in ventilation windows.
- 2.6 Glazing: All windows and doors shall contain clear tempered safety glass, 1/8" minimum thickness
- 2.7 Finish: All steel surfaces shall be painted with rust inhibitive epoxy primer. All exposed interior and exterior steel surfaces shall be painted with one finish coat of industrial acrylic epoxy. Choice of single color of paint as selected by owner from manufacturer's standards.
- 2.8 Canopy: Shall be 14-gauge minimum galvanized steel and standard overhang shall extend 3" beyond the walls. Standard fascia height shall be 6".
- 2.9 Roof: Provide lifting ring(s) welded in roof for onsite lifting of unit. Roof surface shall be 14-gauge galvanized steel sheet. Roof seams shall be continuously welded, caulked and weatherproofed. Roof shall drain to downspout(s).
- 2.10 Insulation: Walls shall be insulated with 2" rigid fiberglass board, R=10. Roof structure fully insulated, R=17.4.
- 2.11 Work counter: One 14-gauge painted steel counter across width of booth. Include one 16" wide steel storage drawer. Counter shall be welded in place. Include one electrical cord access hole install in counter above receptacle.
- 2.12 Electrical: Unit shall be delivered complete with all wiring required for two-lamp shielded fluorescent light with lamps and wall switch, one 110V duplex outlet, heater, a 100A 12-circuit load center with branch circuit breakers and 100A main breaker. All wiring copper No. 12 minimum, enclosed in EMT. All fittings, wiring devices and fixtures UL listed. Ready for site connection. Three wire 240/120V single-phase service required.
- 2.13 Heater: Electrical wall heater shall be fan-forced type including integral thermostat. Minimum heater size shall be 120V/1500W. (Specify optional 208/240V units for larger buildings and cold climates.)
- 2.14 Optional features: Provide items available from manufacturer's optional equipment list at direction of owner/architect to best meet site requirements.



I N T E R N A T I O N A L

SecurMAR

833 Shannon Drive  
Crown Point, IN 46307  
Phone: 219-661-8964  
Fax: 219-661-8965  
sales@securmar.com